



PO FILM PVC FREE Summary of product characteristics

Description

Po film pvc free, UV stabilised for outdoor application and with good flexibility and conformability to curved surfaces.

Printing methods: solvent and UV screenprinting, offset UV, digital printing

Permanent adhesive with good adhesion on irregular substrates, including apolar substrates.

Labels for irregular substrates. Suitable for application on apolar substrates.

Technical data

FACE MATERIAL

Type	Top coated PO film
Colour and Finish	White, gloss
Weight	93 g/m ²
Thickness	95 µ

ADHESIVE

Type	Permanent acrylic
Min. Appl. Temp.	+ 5 °C
Service Temp.	-20°C/+100°C
Shear	Medium
Tack	High
Ultimate Adhesion	Very High

RELEASE BACKING

Type	1 side clay coated kraft paper
Colour and Finish	White
Weight	135 g/m ²
Thickness	135 µ

CHEMICAL RESISTANCE

Detergent	No effect (24Hrs)
Gasoline	No effect (1 Hrs)
SAE20 Motoroil	No effect (24 Hrs)
10% HCl	No effect (10 min)
10% NH4OH	No effect (10 min)

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

Seriart s.r.l.

Via degli Artigiani, 14/C • 26100 Cremona - Italy
Tel. 0372 462501 • Fax 0372 457051
e-mail: info@seri-art.it • http: www.seri-art.it